



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Starry Night / Chameleon Neptune, Panther / Chameleon Saturn
CADRE	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
FOURCHE	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
POTENCE	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
TIGE DE SELLE	Giant D-Fuse, composite, 14mm offset
SELLE	Giant Approach
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano GRX RX-600, 2x11
DÉRAILLEUR AVANT	Shimano GRX RX-810
DÉRAILLEUR ARRIÈRE	Shimano GRX RX-810
FREINS	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
LEVIER DE FREIN	Shimano GRX RX-600 hydraulic
CASSETTE	Shimano 105, 11-speed, 11x34
CHAÎNE	KMC X11SL-1
PÉDALIER	Praxis Alba 2D, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
PÉDALIER	Praxis, press fit
ROUES	
JANTES	Giant P-X2 Disc wheelset
MOYEURS	Giant P-X2 Disc wheelset
RAYONS	Giant P-X2 Disc wheelset
PNEUS	Giant CrossCut AT 1, 700x38c, tubeless
SUPPLÉMENTS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

CARACTÉRISTIQUES

- Cadre: Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
- Fourche: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Manettes: Shimano GRX RX-600, 2x11
- Péda lier: Praxis Alba 2D, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Coloris: Starry Night / Chameleon Neptune, Panther / Chameleon Saturn

Prix: 2.799 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longueur de tube de selle (mm)	430	450	470	490	510
Angle de tube de selle	74,0°	73,5°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	540	550	560	575	585
Longueur du tube de direction (mm)	125	135	150	165	180
Angle du tube de direction	70,0°	71,0°	71,5°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68
Empattement (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051
Longueur des bases (mm)	425 435	425 435	425 435	425 435	425 435
Hauteur du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Hauteur en statique (mm)	724 731	740 747	757 764	774 780	791 797
Largeur de cintre (mm)	420	420	440	440	460
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175
Diamètre des roues	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT Belgique se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles. Les prix sont librement fixés par les revendeurs Giant de ce fait ils n'apparaissent pas sur le site Internet.