



## CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
<b>MOTEUR</b>	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
<b>COMMANDE</b>	Giant RideControl Ergo3, grip integrated remote
<b>ECRAN</b>	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
<b>BATTERIE</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>CHARGEUR</b>	Giant EnergyPak 6A smart charger, 60% in 2:15h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
<b>TAILLES</b>	S, M, L, XL
<b>COLORIS</b>	Messier / Black
<b>CADRE</b>	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
<b>FOURCHE</b>	Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR
<b>AMORTISSEUR</b>	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
<b>CINTRE</b>	Giant Contact 35 Trail, 35x780mm
<b>POIGNÉES</b>	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
<b>POTENCE</b>	Giant Contact SL 35
<b>TIGE DE SELLE</b>	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
<b>SELLE</b>	Giant Romero E
<b>PÉDALES</b>	Flat pedal
DÉRAILLEUR	
<b>MANETTES</b>	Shimano SLX
<b>DÉRAILLEUR AVANT</b>	MRP HD2 co-moulded chain guide
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano SLX, 12-speed, Shadow+
<b>FREINS</b>	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
<b>LEVIERS DE FREIN</b>	Shimano Deore, I-spec EV
<b>CASSETTE</b>	Shimano CS-M6100-12, 10-51T, 12-speed
<b>CHAÎNE</b>	KMC e.12 Turbo, EcoProtege, e-bike optimized
<b>PÉDALIER</b>	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
<b>PÉDALIER</b>	n/a

ROUES	
<b>JANTES</b>	Giant AM30, Tubeless ready, 30mm inner width, 29"
<b>MOYEURS</b>	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
<b>RAYONS</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>PNEUS</b>	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
<b>SUPPLÉMENTS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
<b>ANTI-VOL</b>	Torx 25 Battery Lock with built-in Torque limiter

Prix: 6.099,00 €

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°
Longueur du tube supérieur (mm)	577   575	610   605	637   635	667   665				
Longueur du tube de direction (mm)	95	100	110	120				
Angle du tube de direction	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	117   122,4	117   122,4	117   122,4	117   122,4				
Empattement (mm)	1205   1206	1239   1237	1268   1269	1300   1301				
Longueur des bases (mm)	473   473	473   473	473   473	473   473				
Hauteur du boîtier de pédalier (mm)	30   20	30   20	30   20	30   20				
Stack (mm)	606   601	611   605	621   614	630   624				
Reach (mm)	439   447	457   462	482   489	510   517				
Hauteur en statique (mm)	783   789	775   784	763   770	775   782				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	50	50	60				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	29"	29"	29"	29"				

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT Belgique se réserve le droit de modifier les spécifications sans préavis.